

# BASKET

## FASCIO/BEAM LA

Sospensione decorativa.  
Decorative suspension.

Corpo in lastra d'alluminio tornito verniciato con polveri epossidiche previa fosfatazione. Completa di cavo di sospensione L. 2 m e rosone. Dissipatore in alluminio estruso. Ottica in policarbonato opale. Sorgente luminosa LED. Emissione diretta. Sistema di fissaggio a sospensione. Per installazione a binario: accessorio attacco a binario (cod. TK). Alimentazione elettronica integrata CAE. A richiesta: dimmerabile DALI (cod. DL). Emergenza autonomia 1h/3h.

*Turned aluminium body painted with epoxy powders after phosphating. Complete with suspension cable 2 mt length and ceiling rose. Extruded aluminium heatsink. Opal polycarbonate louver. LED light source. Direct light emission. Suspension mounting system. Track mounting system accessory (cod. TK). Built-in electronic driver CAE. On request: dimmable DALI (code DL). Emergency autonomy 1h/3h.*



Lumen	Watt	Lumen Watt Out	mA	Codice Code	Fascio Beam	K	Alimentazione Power Supply	Colore Colour
4820	42	≤ 114	350	<b>HRBK1</b>	<b>LA:</b> fascio largo wide beam	<b>WW:</b> 2700 <b>W:</b> 3000 <b>X:</b> 3500 <b>N:</b> 4000	-: CAE elettronica electronic  <b>DL:</b> DALI	<b>Standard:</b>
6100	54	≤ 110	450	<b>HRBK2</b>				● <b>WI:</b> White Irazu ● <b>BLL:</b> Black Lava
8700	87	≤ 100	700	<b>HRBK3</b>				<b>Su richiesta /On request:</b> ● <b>SB:</b> Silver Bombalai ● <b>BL:</b> Bronze Lario ● <b>RR:</b> Rust Rame ● <b>BF:</b> Beige Futura ● <b>GK:</b> Gold Karkar ● <b>BT:</b> Blue Telica




A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.  
Lumen: flusso totale in uscita con 3000K CRI90;  
Variazione flusso con CRI85 + 8%, con CRI95 - 8%.  
Watt: potenza di sistema  
Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.  
Lumen: total output flux with 3000K CRI90;  
Flux variation with CRI85 + 8%, with CRI95 - 8%.  
Watt: system power  
Tolerance ± 10%

Ottica LA 90°



H (m)	Ø (m)
1	2.0
2	4.0
3	6.0
4	8.0
5	10