

CENTOTTANTA

FASCIO/BEAM LA

Apparecchio LED da incasso.
Recessed LED downlight.

Corpo in lamiera tornita verniciata con polveri epossidiche bianche previa fosfatizzazione con funzione di dissipatore. Diffusore in policarbonato opale fascio largo (cod. LA). Sorgente luminosa LED. Emissione diretta. Fissaggio ad incasso mediante molle. Alimentazione elettronica separata CAE. A richiesta: dimmerabile DALI (cod. DL). Specificare se con funzione Push Dim (cod. PD). Emergenza autonomia 1h/3h.

Turned sheet metal body painted with white epoxy powder after phosphating with heatsink function. Opal polycarbonate diffuser wide beam (code LA). LED light source. Direct light emission. Recessed fixing system with springs. Separate electronic driver CAE. On request: dimmable DALI (code DL). Push Dim function to be specified (code PD). Emergency autonomy 1h/3h.



Lumen	Watt	Lumen Watt Out	mA	Codice Code	Fascio Beam	K	Alimentazione Power Supply	Colore Colour
2150	18	≤ 120	500	HR1801	LA: fascio largo wide beam	WW: 2700 W: 3000 X: 3500 N: 4000	-: CAE elettronica electronic DL: DALI	Standard:
2550	22	≤ 116	HR1802	● W1: White Irazu ● BLL: Black Lava				
2950	26	≤ 114	HR1803	Su richiesta / On request:				
								● SB: Silver Bombalai ● BL: Bronze Lario ● RR: Rust Rame ● BF: Beige Futura ● GK: Gold Karkar ● BT: Blue Telica




A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.
Lumen: flusso totale in uscita con 3000K CRI90;
Variazione flusso con CRI85 + 8%, con CRI95 - 8%.
Watt: potenza di sistema
Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.
Lumen: total output flux with 3000K CRI90;
Flux variation with CRI85 + 8%, with CRI95 - 8%.
Watt: system power
Tolerance ± 10%

Ottica LA 100°



H (m)	Ø (m)
1	2.4
2	4.8
3	7.2
4	9.5
5	12