

HRAMCT1

HRAMCT2

HRAMCT3

# MINI ALGEBRA TRACK

SCHERMO/DIFFUSER OP | MP

Sistema lineare a binario.

Track linear system


**5Y WARRANTY**  
5% FAILURE RATE

**60.000 h**  
LED LIFETIME L90B10

**100.000 h**  
LED LIFETIME L70B50

Corpo in lamiera d'acciaio pressopiegata verniciata con polveri epossidiche previa fosfatazione. Ottiche in alluminio ad alto rendimento con funzione di dissipatore. Schermo in policarbonato opale (cod. OP) o microprismato (cod. MP). Sorgente luminosa LED. Emissione diretta. Sistema di fissaggio a binario con alimentazione integrata nell'adattatore CAE. A richiesta: dimmerabile DALI (cod. DL).

*Bent sheet steel body painted with epoxy powders after phosphating. High performance aluminium louvers with heatsink function. Opal (code OP) or microprismatic (code MP) polycarbonate diffuser. LED light source. Direct light emission. Track mounting system with built-in electronic driver CAE. On request: dimmable DALI (code DL).*

Lumen	Watt	Lumen Watt Out	mA	Codice Code	Schermo Diffuser	K	Alimentazione Power Supply	Colore Colour
1540	18	≤ 110	500	<b>HRAMCT1</b>	OP: opale opal MP: microprismato microprismatic	<b>WW: 2700</b> <b>W: 3000</b> <b>X: 3500</b> <b>N: 4000</b>	-: CAE elettronica electronic  DL: DALI	<b>Standard:</b> <ul style="list-style-type: none"> <li>● <b>WI:</b> White Irazu</li> <li>● <b>BLL:</b> Black Lava</li> </ul> <b>Su richiesta / On request:</b> <ul style="list-style-type: none"> <li>● <b>SB:</b> Silver Bombalai</li> <li>● <b>BL:</b> Bronze Lario</li> <li>● <b>RR:</b> Rust Rame</li> <li>● <b>BF:</b> Beige Futura</li> <li>● <b>GK:</b> Gold Karkar</li> <li>● <b>BT:</b> Blue Telica</li> </ul>
2310	27	≤ 110	700	<b>HRAMCT2</b>				
3080	28	≤ 110	800	<b>HRAMCT3</b>				





A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.  
Lumen: flusso totale in uscita con 3000K CRI90.  
Variazione flusso con CRI85 + 8%, con CRI95 - 8%.  
Watt: potenza di sistema  
Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.  
Lumen: total output flux with 3000K CRI90.  
Flux variation with CRI85 + 8%, with CRI95 - 8%.  
Watt: system power  
Tolerance ± 10%

Ottica MP 50°

Ottica OP 112°



H (m)	Ø (m)	H (m)	Ø (m)
1	1.0	1	1.0
2	2.0	2	2.0
3	2.8	3	2.8
4	4.0	4	4.0
5	5.0	5	5.0