



Nota/Note  
 Ottiche intercambiabili senza ausilio di utensili  
 Exchangeable optics without using of tools

# MUSE 55 S/10

FASCIO/BEAM SP | ST | MD | LA

Proiettore LED a binario orientabile con ottiche intercambiabili.  
 Adjustable track-mounted LED projector, exchangeable optics.

Corpo in estruso d'alluminio verniciato con polveri epossidiche previa fosfatazione. Dissipatore in alluminio estruso. Ottica in policarbonato metallizzato fascio largo (cod. LA) fascio medio (cod. MD) fascio stretto (cod. ST) fascio spot (cod. SP). Sorgente luminosa LED. Emissione diretta. Sistema di fissaggio a binario con alimentazione integrata nell'adattatore CAE. A richiesta: dimmerabile DALI (cod. DL).

Extruded aluminium body painted with epoxy powders after phosphating. Extruded aluminium heatsink. Metallized polycarbonate louver wide beam (code LA) medium beam (code MD) narrow beam (code ST) spot beam (code SP). LED light source. Direct light emission. Track mounting system with built-in electronic driver CAE. On request: dimmable DALI (code DL).



Lumen	Watt	Lumen Watt Out	mA	Codice Code	Fascio Beam	K	Alimentazione Power Supply	Colore Colour
1100	9	≤ 122	250	HRM6S11	SP: fascio spot spot beam	WW: 2700 W:3000 X:3500 N:4000	-: CAE elettronica electronic  DL: DALI	<b>Standard:</b> ● <b>WI:</b> White Irazu ● <b>BLL:</b> Black Lava  <b>Su richiesta /On request:</b> ● <b>SB:</b> Silver Bombalai ● <b>BL:</b> Bronze Lario ● <b>RR:</b> Rust Rame ● <b>BF:</b> Beige Futura ● <b>GK:</b> Gold Karkar ● <b>BT:</b> Blue Telica
1550	13	≤ 119	350	HRM6S12	ST: fascio stretto narrow beam			
2150	18,5	≤ 116	500	HRM6S13	MD: fascio medio medium beam LA: fascio largo wide beam			



A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.  
 Lumen: flusso totale in uscita con 3000K CRI90;  
 Variazione flusso con CRI85 + 8%, con CRI95 - 8%.  
 Watt: potenza di sistema  
 Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.  
 Lumen: total output flux with 3000K CRI90;  
 Flux variation with CRI85 + 8%, with CRI95 - 8%.  
 Watt: system power  
 Tolerance ± 10%

