

Opalia



Decorative suspension lighting fitting



On request

IT

Apparecchio decorativo per installazione a sospensione. Corpo diffusore in policarbonato opale. Terminali di chiusura in alluminio torniti. Sorgente luminosa LED multichip. Alimentatore incorporato. Fornito completo di sospensioni in acciaio regolabili e cavo di alimentazione L=2m. Rosone per collegamento elettrico non incluso, da ordinare separatamente.

ES

Luminaria decorativa para instalación en suspensión. Cuerpo difusor de policarbonato opal. Tapas de aluminio torneado. Fuente de iluminación LED. Balasto integrado. Cables de suspensión de acero ajustables y cable de alimentación L=2m incluidos. Roseta electrificada no incluida, a pedir por separada.

EN

Decorative suspension lighting fitting. Opal polycarbonate diffuser body. Turned aluminium end covers. LED light source. Integrated driver. Supplied complete with adjustable steel suspensions and power cable L = 2m. Rose ceiling for electrical connection not included, to be ordered separately.

DE

Dekoratives Hängebeleuchtungsgerät. Diffusor Körper aus Opalpolycarbonat. Endkappen aus gedrehtem Aluminium. LED-Lichtquelle. Integrierter Treiber. Komplett mit verstellbaren Stahlabhängungen und Netzkabel L = 2m. Deckenbefestigung für elektrische Verbindung nicht enthalten, separat zu bestellen.

FR

Appareil décoratifs en suspension. Corp diffusant en polycarbonate opal. Terminaux de fermeture en aluminium décollété. Source lumineuse LED. Alimentation avec driver intégré. Fourni avec fils de suspensions en acier réglables et câble d'alimentation L= 2mt. Patère et branchement électrique exclus, à commander séparément.

01



02



OPALIA 4000 K

Code	Size	Lumen Out	Watt Tot	K	Beam angle	Driver Type	Driver	Colour
YOP11N	01	6894	60	4000	D	ON/OFF	1	○
YOP15N	02	7954	69	4000	D	ON/OFF	1	○

OPALIA 3000 K

Code	Size	Lumen Out	Watt Tot	K	Beam angle	Driver Type	Driver	Colour
YOP11W	01	6383	60	3000	D	ON/OFF	1	○
YOP15W	02	7365	69	3000	D	ON/OFF	1	○


OPALIA STANDARD COLOUR SELECTION

● **WI** | White Irazu ● **BLL** | Black Lava


OPALIA ON REQUEST COLOUR SELECTION

● **BF** | Beige Futuna ● **SB** | Silver Bombalai ● **GK** | Gold Karkar
 ● **BL** | Bronze Lario ● **RR** | Rust Rame ● **BT** | Blue Telica

OPALIA BEAM ANGLE | DIMENSIONS




Size	X [mm]	Y [mm]	Z [mm]	Kg
01	1210	ø 83	ø 89	3,6
02	1590	ø 83	ø 89	4,5




Min and Max room temperature: -20°+45° C.

OPALIA ACCESSORIES



KT10301 + ○ COLOUR


Rose ceiling for installation with ceiling panel, remote driver.



YOP11-KRO (L 1210) + ○ COLOUR

YOP15-KRO (L 1590) + ○ COLOUR

Rose ceiling for brick installation H45 mm with driver housing.



KT10501 + ○ COLOUR

Rose ceiling for brick installation without driver housing. For remote driver 24 Volt max 5 mt.