

REAL

FASCIO/BEAM LA

Sospensione decorativa.
Decorative suspension.

5Y WARRANTY
5% FAILURE RATE

60.000 h
LED LIFETIME L70B10

100.000 h
LED LIFETIME L70B50

Corpo in estruso d'alluminio verniciato con polveri epossidiche previa fosfatazione. Completa di cavo di sospensione L. 2 m e rosone. Dissipatore in alluminio estruso. Ottica in policarbonato opale. Sorgente luminosa LED. Emissione diretta e indiretta. Sistema di fissaggio a sospensione. Per installazione a binario: accessorio attacco a binario (cod. TK). Alimentazione elettronica integrata CAE. A richiesta: dimmerabile DALI (cod. DL). Emergenza autonomia 1h/3h.

Extruded aluminium body painted with epoxy powders after phosphating. Complete with suspension cable 2 mt lenght and ceiling rose. Extruded aluminium heatsink. Opal polycarbonate louver. LED light source. Direct and indirect light emission. Suspension mounting system. Track mounting system accessory (cod. TK). Built-in electronic driver CAE. On request: dimmable DALI (code DL). Emergency autonomy 1h/3h.

Lumen	Watt	Lumen Watt Out	mA	Codice Code	Fascio Beam	K	Alimentazione Power Supply	Colore Colour
1410 + 1330	11 + 11	≤ 128	450	HRRE1	LA: fascio largo wide beam	WW: 2700 W: 3000 X: 3500 N: 4000	-: CAE elettronica electronic DL: DALI	Standard: ● WI: White Irazu ● BLL: Black Lava Su richiesta / On request: ● SB: Silver Bombalio ● BL: Bronze Lario ● RR: Rust Rame ● BF: Beige Futura ● GK: Gold Karkar ● BT: Blue Telica


CE
IP44
>90 CRI
3SDCM
IP44 EN 60529
IK 07 EN 60068
230 V 2014/25/EU
50/60 Hz
850° EN 60695
RG 0 EN 62471
DL DALI
DIM W
>80 CRI
>95 CRI
VIVID PLUS
VEG PLUS
WHITE PLUS
MEAT PLUS
EM
TK

A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.
Lumen: flusso totale in uscita con 3000K CRI90;
Variazione flusso con CRI85 + 8%, con CRI95 - 8%.
Watt: potenza di sistema
Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.
Lumen: total output flux with 3000K CRI90;
Flux variation with CRI85 + 8%, with CRI95 - 8%.
Watt: system power
Tolerance ± 10%

Ottica Diretta 53° / Indiretta 70°



H (m)	Ø (m)	H (m)	Ø (m)
1	1.0	5	7.0
2	2.0	4	5.6
3	2.8	3	4.2
4	4.0	2	2.8
5	5.0	1	1.4