

SOO L

SCHERMO/DIFFUSER OP | MP

Sistema LED lineare 24 Volt.
LED linear system 24 Volt.

Corpo in estruso di alluminio verniciato con polveri epossidiche previa fosfatazione. Ottica microprismata trasparente (codice MP), opale (codice OP). Fornito completo di cavo di alimentazione lunghezza 2 m. Sorgente luminosa LED. Emissione diretta. Fissaggio a plafone o incasso a mezzo viti. Alimentazione 24 volt esterna CAE. Alimentatore non incluso, da ordinare separatamente. A richiesta dimmerabile DALI.

Extruded aluminium body painted with epoxy powder after phosphating. Microprismatic polycarbonate louver (code MP) opal (code OP). Complete with power supply cable 2 m. length. LED light source. Direct light emission. Ceiling mounting system or recessed with screws. Separate electronic driver 24 Volt CAE. Driver not included, to be ordered separately. On request: dimmable DALI (code DL).



Lumen	Watt	Lumen Watt Out	Volt	Codice Code	Schermo Diffuser	K	Alimentazione Power Supply	Colore Colour
2350	19	≤ 123	24	HRSOL11	OP: opale opal MP: microprismato microprismatic	WW: 2700 W: 3000 X: 3500 N: 4000	--: CAE elettronica electronic DL: DALI	Standard: ● W1: White Irazu ● BLL: Black Lava Su richiesta /On request: ● SB: Silver Bombalai ● BL: Bronze Lario ● RR: Rust Rame ● BF: Beige Futura ● GK: Gold Karkar ● BT: Blue Telica
4700	38	≤ 123	24	HRSOL21				
7050	57	≤ 123	24	HRSOL31				
4700	38	≤ 123	24	HRSOL12				
9400	76	≤ 123	24	HRSOL22				
14100	114	≤ 123	24	HRSOL32				





A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.
Lumen: flusso totale in uscita con 3000K CRI90.
Variazione flusso con CRI85 + 8%, con CRI95 - 8%.
Watt: potenza di sistema
Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.
Lumen: total output flux with 3000K CRI90.
Flux variation with CRI85 + 8%, with CRI95 - 8%.
Watt: system power
Tolerance ± 10%

Ottica MP 50°

Ottica OP 112°



H (m)	Ø (m)	H (m)	Ø (m)
1	1.0	1	1.0
2	2.0	2	2.0
3	2.8	3	2.8
4	4.0	4	4.0
5	5.0	5	5.0