



SOTTILE TRACK

FASCIO/BEAM MD | LA | BT

Sistema lineare a binario.
Track linear system

Corpo in lamiera pressopiegata verniciata con polveri epossidiche previa fosfatazione. Dissipatore in alluminio estruso. Ottica in metacrilato lenticolare fascio largo (cod. LA) fascio medio (cod. MD) fascio doppio asimmetrico (cod. BT). Sorgente luminosa LED. Emissione diretta. Sistema di fissaggio a binario (adattatore incluso). Alimentazione elettronica integrata nel corpo lampada CAE. A richiesta: dimmerabile DALI (cod. DL).

Bent sheet metal body painted with epoxy powders after phosphating. Extruded aluminium heatsink. Lenticular methacrylate louver wide beam (code LA) medium beam (code MD) asymmetric double beam (code BT). LED light source. Direct light emission. Track mounting system (adapter included). LED light source. Direct light emission. Track mounting system (adapter included). Built-in electronic driver in the body CAE. On request: dimmable DALI (code DL).



Lumen	Watt	Lumen Watt Out	mA	Codice Code	Fascio Beam	K	Alimentazione Power Supply	Colore Colour
3160	26,5	≤ 119	700	HRSTTR1	MD: fascio medio medium beam	WW: 2700 W:3000 X:3500 N:4000	-: CAE elettronica electronic DL: DALI	Standard: ● W1: White Irazu ● BLL: Black Lava Su richiesta /On request: ● SB: Silver Bombalai ● BL: Bronze Lario ● RR: Rust Rame ● BF: Beige Futura ● GK: Gold Karkar ● BT: Blue Telica
6320	53	≤ 119	700	HRSTTR2	LA: fascio largo wide beam			
6320	53	≤ 119	700	HRSTTR3	BT: fascio doppio asimmetrico Asymmetric batwing beam			



A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.
Lumen: flusso totale in uscita con 3000K CRI90;
Variazione flusso con CRI85 + 8%, con CRI95 - 8%.
Watt: potenza di sistema
Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.
Lumen: total output flux with 3000K CRI90;
Flux variation with CRI85 + 8%, with CRI95 - 8%.
Watt: system power
Tolerance ± 10%

