

Nota/Note
Ottiche intercambiabili senza ausilio di utensili
Exchangeable optics without using of tools

TATI

FASCIO/BEAM SP | ST | MD | LA

Sospensione decorativa con ottiche intercambiabili.
Decorative suspension with exchangeable optics.

Corpo in lastra d'alluminio tornito verniciato con polveri epossidiche previa fosfatazione. Completa di cavo di sospensione L. 2 m e rosone. Dissipatore in alluminio estruso. Ottica in policarbonato metallizzato fascio largo (cod. LA) fascio medio (cod. MD) fascio stretto (cod. ST) fascio spot (cod. SP). Sorgente luminosa LED. Emissione diretta. Sistema di fissaggio a sospensione. Per installazione a binario: accessorio attacco a binario (cod. TK). Alimentazione elettronica integrata CAE. A richiesta: dimmerabile DALI (cod. DL).

Turned aluminium body painted with epoxy powders after phosphating. Complete with suspension cable 2 mt length and ceiling rose. Extruded aluminium heatsink. Metallized polycarbonate louver wide beam (code LA) medium beam (code MD) narrow beam (code ST) spot beam (code SP). LED light source. Direct light emission. Suspension mounting system. Track mounting system accessory (cod. TK). Built-in electronic driver CAE. On request: dimmable DALI (code DL).



Lumen	Watt	Lumen Watt Out	mA	Codice Code	Fascio Beam	K	Alimentazione Power Supply	Colore Colour
890	7	≤ 127	200	HRTA1	SP: fascio spot spot beam	WW: 2700 W: 3000 X: 3500 N: 4000	-: CAE elettronica electronic DL: DALI	Standard:
1100	9	≤ 122	250	HRTA2	ST: fascio stretto narrow beam			● WL: White Irazu ● BLL: Black Lava
1350	11	≤ 121	300	HRTA3	MD: fascio medio medium beam			Su richiesta / On request:
					LA: fascio largo wide beam			● SB: Silver Bombalai ● BL: Bronze Lario ● RR: Rust Rame ● BF: Beige Futura ● GK: Gold Karkar ● BT: Blue Telica



A richiesta | On request

Temperatura ambiente min. - max: -10°+40° C.
Lumen: flusso totale in uscita con 3000K CRI90.
Variazione flusso con CRI85 + 8%, con CRI95 - 8%.
Watt: potenza di sistema
Tolleranza ± 10%





Min and Max room temperature: -10°+40° C.
Lumen: total output flux with 3000K CRI90.
Flux variation with CRI85 + 8%, with CRI95 - 8%.
Watt: system power
Tolerance ± 10%

Ottica SP 15°

Ottica ST 25°

Ottica MD 40°

Ottica LA 60°



H (m)	Ø (m)	H (m)	Ø (m)	H (m)	Ø (m)	H (m)	Ø (m)
1	0.3	1	0.4	1	0.7	1	1.1
2	0.5	2	0.9	2	1.5	2	2.3
3	1.7	3	1.3	3	2.2	3	3.5
4	1.0	4	1.8	4	2.9	4	4.6
5	1.2	5	2.2	5	3.6	5	5.8