



Nota/Note  
 Ottiche intercambiabili senza ausilio di utensili  
 Exchangeable optics without using of tools

# TUBÌ S

FASCIO/BEAM SP | ST | MD | LA

Sospensione tubolare decorativa Ø 55.  
 Decorative tubular suspension Ø 55.

Corpo in estruso d'alluminio verniciato con polveri epossidiche previa fosfatazione. Dissipatore in alluminio estruso. Ottica in policarbonato metallizzato fascio largo (cod. LA) fascio medio (cod. MD) fascio stretto (cod. ST) fascio spot (cod. SP). Sorgente luminosa LED. Emissione diretta. Sistema di fissaggio a sospensione (completo di cavo L. 2 mt e rosone) o a plafone. Alimentazione elettronica integrata CAE. A richiesta: dimmerabile DALI (cod. DL) specificare se con funzione PUSH DIM (cod. PD). \* Tubi S100 DALI alimentazione remota.

Extruded aluminium body painted with epoxy powders after phosphating. Extruded aluminium heatsink. Metallized polycarbonate louver wide beam (code LA) medium beam (code MD) narrow beam (code ST) spot beam (code SP). LED light source. Direct light emission. Suspension mounting system (complete with cable 2 mt lenght and ceiling rose) or ceiling mounting system. Built-in electronic driver CAE. On request: dimmable DALI (code DL) PUSH DIM function (code PD) to be requested. \* Tubi S100 DALI remote power supply.

**5Y WARRANTY**  
5% FAILURE RATE

**60.000 h**  
LED LIFETIME L90B10

**100.000 h**  
LED LIFETIME L70B50

Lumen	Watt	Lumen Watt Out	mA	Codice Code	Fascio Beam	K	Alimentazione Power Supply	Colore Colour
<b>TUBÌ S100*</b>								
1100	9	≤ 122	250	<b>HRTS11</b>				
1550	13	≤ 119	350	<b>HRTS12</b>				
<b>TUBÌ S200</b>								
1100	9	≤ 122	250	<b>HRTS21</b>				
1550	13	≤ 119	350	<b>HRTS22</b>				
<b>TUBÌ S300</b>								
1100	9	≤ 122	250	<b>HRTS31</b>	<b>SP:</b> fascio spot spot beam	<b>WW: 2700</b> <b>W:3000</b> <b>X:3500</b> <b>N:4000</b>	<b>--:</b> CAE elettronica electronic	<b>DL:</b> DALI
1550	13	≤ 119	350	<b>HRTS32</b>	<b>ST:</b> fascio stretto narrow beam			
1850	16	≤ 116	450	<b>HRTS33</b>	<b>MD:</b> fascio medio medium beam			
<b>TUBÌ S400</b>								
1100	9	≤ 122	250	<b>HRTS41</b>	<b>LA:</b> fascio largo wide beam			
1550	13	≤ 119	350	<b>HRTS42</b>				
1850	16	≤ 116	450	<b>HRTS43</b>				
<b>TUBÌ S500</b>								
1100	9	≤ 122	250	<b>HRTS51</b>				
1550	13	≤ 119	350	<b>HRTS52</b>				
1850	16	≤ 116	450	<b>HRTS53</b>				

**Standard:**

- **WL:** White Irazu
- **BLL:** Black Lava

**Su richiesta /On request:**

- **SB:** Silver Bombalai
- **BL:** Bronze Lario
- **RR:** Rust Rame
- **BF:** Beige Futura
- **GK:** Gold Karkar
- **BT:** Blue Telica

CE, >90 CRI, 3SDCM, IP44 EN 60529, IK 07 EN 60068  
 230 V 201425UE, 50/60 Hz, 850° EN 60495, RG 0 EN 62471  
 DL DALI, PD PUSH DIM, DIM W, >80 CRI, >95 CRI  
 VIVID PLUS, VEG PLUS, WHITE PLUS, MEAT PLUS

A richiesta / On request

Temperatura ambiente min. - max: -10°+40° C.  
 Lumen: flusso totale in uscita con 3000K CRI90;  
 Variazione flusso con CRI85 + 8%, con CRI95 - 8%.  
 Watt: potenza di sistema  
 Tolleranza ± 10%

Min and Max room temperature: -10°+40° C.  
 Lumen: total output flux with 3000K CRI90;  
 Flux variation with CRI85 + 8%, with CRI95 - 8%.  
 Watt: system power  
 Tolerance ± 10%

